



	Dream Nano F	Dream Nano C	Dream Sub
POWER HANDLING	80 Watts (120W peak)	80 Watts (120W peak)	50 watts RMS / 120 peak
FREQUENCY RESPONSE	65 Hz – 20 KHz	70 Hz – 20 KHz	Adjustable 35Hz – 150Hz
SENSITIVITY (+/- 3db)	92db	90db	
IMPEDENCE	4 Ohm	4 Ohm	4 Ohm
DRIVER COMPLIMENT	2 way DRAV FIG.	2 way DRAV FIG.	
WOOFER	One 3" PP Woofer-transfer cone, 20mm ASV voice coil, Y30 ferrite magnet, NOMEX damper	Two 3" Woofer-transfer cone, 20mm ASV voice coil, Y30 ferrite magnet, NOMEX damper	One 6" Woofer
TWEETER	1" black silk diaphragm, 25mm KSV/CCAW voice coil, Space freezing magnetic liquid technology, N42 neodymium magnet	1" black silk diaphragm, 25mmK SV/CCAW voice coil, Space freezing magnetic liquid technology, N42 neodymium magnet	
CROSSOVER FREQUENCY	3,200 Hz	2,700 Hz	
PHASE ALIGNMENT			0-180
LINE INPUT			Yes
POWER CONNECTION			110v or 220v
VOLUME CONTROL			yes
DIMENSIONS (H X W X D)	100x10x9.8 Cm Cm (39.3 x 4 x 3.8 In)	33x10x9.8 Cm (13 x 4 x 3.8 In)	20 x 20x 29 Cm (7.9 x 7.9 x 11 In)
WEIGHT	6.2 Kg (12.4 lbs)	2.4 Kg (2.4 lbs)	5.5 Kg (12.5 lb)
FINISH	Any color	Any color	Any color
GRILLE	Black	Black	Black
CARTON CONTAINS	2 front speakers	1 center speaker	1 subwoofer

Design and specifications are subject to change without notice.

www.pure-acoustics.com



Technical Specifications

	Junior F	Junior C	Junior S
POWER HANDLING	175 Watt	140 Watt	140 Watt
FREQUENCY	44Hz - 22Khz	65Hz - 20Khz	65Hz-20Khz
SENSITIVITY (+/- 3DB)	90db	88db	88db
NOMINAL IMPEDANCE	8 Ohm	8 Ohm	8 Ohm
DRIVER COMPLEMENT	2 way 3 drivers bass reflex	2 way DRAV FIG. magnetic shielding, bass reflex	2 way DRAV FIG.
WOOFER	Two 6.5" (162mm) woofer PPC	Two 4" (100-mm) midwoofer PPC.	One 4" (100-mm) midwoofer PPC.
TWEETER	1" (25mm) silk dome tweeter	5/8" (14mm) New D tweeter	5/8" (14mm) New D tweeter
CROSSOVER FREQUENCY	3000 Hz	2,700 Hz	3,500 Hz
DIMENSIONS (HXWXD)	75x20x32 Cm	14.5x48x17 Cm	24x14.5x17Cm
WEIGHT	8.75 Kg (20Lbs) each	3.7 Kg (8.4 Lbs)	1.9 Kg (4.3 Lbs) each
FINISH	Black, Silver, Cherry, Beech, Mahogany, Maple	Black, Silver, Cherry, Beech, Mahogany, Maple	Black, Silver, Cherry, Beech, Mahogany, Maple
GRILLE	Black/Gray cloth	Black/Gray cloth	Black/Gray cloth

Design and specifications are subject to change without notice.

Pure Acoustics, Inc.
18 Fuller Place, Brooklyn NY 11215
USA
718.788.4411
www.pure-acoustics.com



	Spark F	Spark C	Spark S
POWER HANDLING	200 Watt	140 Watt	140 Watt
FREQUENCY	45Hz - 22Khz	55Hz - 20Khz	60Hz-20Khz
SENSITIVITY (+/- 3DB)	90db	86db	85db
NOMINAL IMPEDANCE	8 Ohm	8 Ohm	8 Ohm
DRIVER COMPLEMENT	2 way 3 drivers bass reflex	2 way DRAV FIG. magnetic shielding, bass reflex	2 way DRAV FIG.
WOOFER	Two 6.5" (162mm) woofer PPC	Two 4" (100-mm) midwoofer PPC.	One 4" (100-mm) midwoofer PPC.
TWEETER	1" (25mm) silk dome tweeter	1" (25mm) silk dome tweeter	1" (25mm) silk dome tweeter
CROSSOVER FREQUENCY	2,500 Hz	3,000 Hz	3,000 Hz
DIMENSIONS (HXWXD)	87.5 x 21.5x 25 Cm	14.5 x 37 x 17 Cm	24 x 14.5 x 17Cm
WEIGHT	10.5 Kg each	3 Kg	2.1 Kg each
FINISH	Black, Silver, Cherry, Beech, Mahogany, Maple	Black, Silver, Cherry, Beech, Mahogany, Maple	Black, Silver, Cherry, Beech, Mahogany, Maple
GRILLE	Black/Gray cloth	Black/Gray cloth	Black/Gray cloth
CARTON DIMENSIONS (H X W X D)	96.3 x 70.7 x 32.2 Cm		
CARTON WEIGHT	31.5 Kg		
CARTON CONTAINS	5 pcs set , 2 front + 2 rear + 1 center speaker		

*Design and specifications are subject to change without notice.
www.pure-acoustics.com*



TECHNICAL SPECIFICATIONS

	RB 1200	RB 1150
POWER HANDLING	200 Watt	175 Watt
FREQUENCY	Adjustable 30Hz-250Hz	Adjustable 35Hz-150Hz
PHASE ALIGNMENT	NA	NA
NOMINAL	8 Ohm	8 Ohm
POWER	110 or 220 Volts	110 or 220 Volts
AUTO ON/OFF	Yes	Yes
VOLUME CONTROL	Yes	Yes
LINE INPUT	RCA connector	RCA connector
SPEAKER INPUT/OUTPUT	Low level / hi level	Low level / hi level
DIMENSIONS (HXWxD)	43x43x42.5 Cm	38x36x37 Cm
FINISH	Black, Silver, Cherry, Beech	Black, Silver, Cherry, Beech
GRILLE	Black cloth	Black cloth

Design and specifications are subject to change without notice.



Pure Acoustics, Inc. 18 Fuller Place Brooklyn NY 11215 USA 718.788.4411

www.pure-acoustics.com



	Dream Nano F	Dream Nano C	Dream Sub
POWER HANDLING	80 Watts (120W peak)	80 Watts (120W peak)	50 watts RMS / 120 peak
FREQUENCY RESPONSE	65 Hz – 20 KHz	70 Hz – 20 KHz	Adjustable 35Hz – 150Hz
SENSITIVITY (+/- 3db)	92db	90db	
IMPEDENCE	4 Ohm	4 Ohm	4 Ohm
DRIVER COMPLIMENT	2 way DRAV FIG.	2 way DRAV FIG.	
WOOFER	One 3" PP Woofer-transfer cone, 20mm ASV voice coil, Y30 ferrite magnet, NOMEX damper	Two 3" Woofer-transfer cone, 20mm ASV voice coil, Y30 ferrite magnet, NOMEX damper	One 6" Woofer
TWEETER	1" black silk diaphragm, 25mm KSV/CCAW voice coil, Space freezing magnetic liquid technology, N42 neodymium magnet	1" black silk diaphragm, 25mmK SV/CCAW voice coil, Space freezing magnetic liquid technology, N42 neodymium magnet	
CROSSOVER FREQUENCY	3,200 Hz	2,700 Hz	
PHASE ALIGNMENT			0-180
LINE INPUT			Yes
POWER CONNECTION			110v or 220v
VOLUME CONTROL			yes
DIMENSIONS (H X W X D)	100x10x9.8 Cm Cm (39.3 x 4 x 3.8 In)	33x10x9.8 Cm (13 x 4 x 3.8 In)	20 x 20x 29 Cm (7.9 x 7.9 x 11 In)
WEIGHT	6.2 Kg (12.4 lbs)	2.4 Kg (2.4 lbs)	5.5 Kg (12.5 lb)
FINISH	Any color	Any color	Any color
GRILLE	Black	Black	Black
CARTON CONTAINS	2 front speakers	1 center speaker	1 subwoofer

Design and specifications are subject to change without notice.

www.pure-acoustics.com



	Dream Tower F	Dream Tower C	Dream Tower S
POWER HANDLING	140 Watts	120 Watts	120 Watts
FREQUENCY RESPONSE	60 Hz – 20 KHz	75 Hz – 20 KHz	75 Hz – 20 KHz
SENSITIVITY (+/- 3db)	92db	90db	90db
IMPEDENCE	4 Ohm	4 Ohm	4 Ohm
DRIVER COMPLIMENT	2 way DRAV FIG.	2 way DRAV FIG.	2 way DRAV FIG.
WOOFER	Four 3" PP Woofer-transfer cone, 20mmASV voice coil, Y30 ferrite magnet, NOMEX damper	One 3" Woofer-transfer cone, 20mmASV voice coil, Y30 ferrite magnet, NOMEX damper	One 3" Woofer-transfer cone, 20mmASV voice coil, Y30 ferrite magnet, NOMEX damper
TWEETER	1" black silk diaphragm, 25mmKSV/CCAW voice coil, Space freezing magnetic liquid technology, N42 neodymium magnet	1" black silk diaphragm, 25mmKSV/CCAW voice coil, Space freezing magnetic liquid technology, N42 neodymium magnet	1" black silk diaphragm, 25mmKSV/CCAW voice coil, Space freezing magnetic liquid technology, N42 neodymium magnet
CROSSOVER FREQUENCY	3,200 Hz	2,700 Hz	2,700 Hz
DIMENSIONS (H X W X D)	100x10x9.8 Cm Cm (39.3 x 4 x 3.8 In)	33x10x9.8 Cm (13 x 4 x 3.8 In)	25x10x9.8 Cm (9.8 x 4 x 3.8 In)
WEIGHT	6.2 Kg (12.4 lbs)	2.4 Kg (2.4 lbs)	1.9 Kg (2.2 lbs)
FINISH	Any color	Any color	Any color
GRILLE	Black	Black	Black
CARTON DIMENSIONS (H X W X D)	19x104x33 Cm (7x41x13 In)	19x42x16 Cm (7x16.5x6.3 In)	21.7x33x18 Cm (8.25x13x7.2 In)
CARTON WEIGHT	13.5 Kg (30 lbs)	3 Kg (6.8 lbs)	3 Kg (6.8 lbs)
CARTON CONTAINS	2 front towers speakers	1 center speaker	2 satellite speakers

Design and specifications are subject to change without notice.
www.pure-acoustics.com



	Noblell F	Noblell C	Noblell S
POWER HANDLING	185 Watt	150 Watt	150 Watt
FREQUENCY	48Hz – 20Khz	60Hz - 20Khz	65Hz-20Khz
SENSITIVITY (+/- 3DB)	89db	87db	85db
IMPEDANCE	4 Ohm	4 Ohm	4 Ohm
DRIVER COMPLEMENT	3 way, 4 drivers	2 way, 3 drivers. magnetic shielding	2 way, 2 drivers
WOOFER	Two 5" woofer PC CONE for low frequencies	Two 4" midwoofer- driver FAC CONE	One 4" midwoofer- driver FAC CONE
MIDRANGE	One 5" Mid-Driver PC CON		
TWEETER	1" (25mm) silk SCOS dome	1" (25mm) silk SCOS dome	1" (25mm) silk SCOS dome
CROSSOVER FREQUENCY	1,000 / 3,500 Hz	2,700 Hz	3,500 Hz
DIMENSIONS (HXWXD)	106x19.5x21.5 Cm	14x35x14 Cm	30x14x14 Cm
WEIGHT	11.8 Kg (26 Lbs) each	3.9 Kg (6.1 Lbs)	2.8 Kg (5.6 Lbs) each
FINISH	high-gloss Silver, Black, red	high-gloss Silver, Black, red	high-gloss Silver, Black, red
GRILLE	Black cloth	Black cloth	Black cloth

Design and specifications are subject to change without notice.

www.pure-acoustics.com



	Spark F	Spark C	Spark S
POWER HANDLING	200 Watt	140 Watt	140 Watt
FREQUENCY	45Hz - 22Khz	55Hz - 20Khz	60Hz-20Khz
SENSITIVITY (+/- 3DB)	90db	86db	85db
NOMINAL IMPEDANCE	8 Ohm	8 Ohm	8 Ohm
DRIVER COMPLEMENT	2 way 3 drivers bass reflex	2 way DRAV FIG. magnetic shielding, bass reflex	2 way DRAV FIG.
WOOFER	Two 6.5" (162mm) woofer PPC	Two 4" (100-mm) midwoofer PPC.	One 4" (100-mm) midwoofer PPC.
TWEETER	1" (25mm) silk dome tweeter	1" (25mm) silk dome tweeter	1" (25mm) silk dome tweeter
CROSSOVER FREQUENCY	2,500 Hz	3,000 Hz	3,000 Hz
DIMENSIONS (HXWXD)	87.5 x 21.5x 25 Cm	14.5 x 37 x 17 Cm	24 x 14.5 x 17Cm
WEIGHT	10.5 Kg each	3 Kg	2.1 Kg each
FINISH	Black, Silver, Cherry, Beech, Mahogany, Maple	Black, Silver, Cherry, Beech, Mahogany, Maple	Black, Silver, Cherry, Beech, Mahogany, Maple
GRILLE	Black/Gray cloth	Black/Gray cloth	Black/Gray cloth
CARTON DIMENSIONS (H X W X D)	96.3 x 70.7 x 32.2 Cm		
CARTON WEIGHT	31.5 Kg		
CARTON CONTAINS	5 pcs set , 2 front + 2 rear + 1 center speaker		

*Design and specifications are subject to change without notice.
www.pure-acoustics.com*



TECHNICAL SPECIFICATIONS

	RB 1200	RB 1150
POWER HANDLING	200 Watt	175 Watt
FREQUENCY	Adjustable 30Hz-250Hz	Adjustable 35Hz-150Hz
PHASE ALIGNMENT	NA	NA
NOMINAL	8 Ohm	8 Ohm
POWER	110 or 220 Volts	110 or 220 Volts
AUTO ON/OFF	Yes	Yes
VOLUME CONTROL	Yes	Yes
LINE INPUT	RCA connector	RCA connector
SPEAKER INPUT/OUTPUT	Low level / hi level	Low level / hi level
DIMENSIONS (HXWXD)	43x43x42.5 Cm	38x36x37 Cm
FINISH	Black, Silver, Cherry, Beech	Black, Silver, Cherry, Beech
GRILLE	Black cloth	Black cloth

Design and specifications are subject to change without notice.



Pure Acoustics, Inc. 18 Fuller Place Brooklyn NY 11215 USA 718.788.4411

www.pure-acoustics.com